

TURCO ZINCTONE

ACID BRIGHTENER FOR ZINC AND COPPER ALLOYS

1. DESCRIPTION:

TURCO® ZINCTONE is a clear, red liquid formulated to remove light oxide films and brighten zinc and zinc alloy parts, such as carburetors fuel pumps and die-cast by immersion methods.

The product dramatically brightens brass and copper alloys.

TURCO® ZINCTONE restores the original lustre to zinc alloys, and is frequently used on zinc components that require visible and fluorescent penetrant inspection prior to re-assembly and for penetrant inspection of raw zinc die castings prior to machining.

2. BENEFITS:

TURCO® ZINCTONE offers these benefits:

1. Non-flammable in concentrate or solution form.
2. Used at ambient temperature.
3. Readily soluble in tap water at recommended concentrations.
4. Easily rinsed from parts with water.
5. Solution is controlled by simple titration.
6. Extremely effective on copper or brass alloys.

3. USE INSTRUCTIONS:

TANKS: Tanks and associated equipment must be fabricated from stainless steel or other acid resistant materials. Mild steel tanks are not recommended.

PRECLEANING: Parts must be free of all contamination and oxides prior to immersion in **TURCO® ZINCTONE**. Your HENKEL REPRESENTATIVE can recommend a suitable pre-cleaner based upon your production requirements.

3. USE INSTRUCTIONS:

MIXING: Dilute **TURCO® ZINCTONE** at the ratio of 1 part of **TURCO® ZINCTONE** to 3 parts of clean water. Mix thoroughly. Immerse clean parts in **TURCO® ZINCTONE** solution for 50 to 60 seconds.

RINSING: Rinse parts by high volume spray methods immediately after removal from cleaner solution. In some cases, a neutralising rinse of a mild alkali may be advantageous. Consult your HENKEL REPRESENTATIVE for recommendation regarding a **TURCO®** alkaline rinse process.

DRYING: Dry parts by any conventional method as soon as possible after rinsing.

4. DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your local HENKEL REPRESENTATIVE or HENKEL MATERIAL SAFETY DATA SHEET for additional disposal information.

5. CAUTION:

TURCO® ZINCTONE contains sulphuric acid, nitric acid and chromate. Avoid contact with eyes, skin and clothing. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield, goggles, gloves, boots and apron made from acid resistant neoprene should be worn when handling this product.

Always add **TURCO® ZINCTONE** to water.

Transport and store in closed containers at temperatures from 0° to 50°C away from caustic materials.

Refer to container label or HENKEL MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.